wherein the local oscillator outputs an oscillation signal having a frequency band of at least 847 to 505 MHz, and a dividing rate of the second programmable divider is 1/3, and wherein a dividing rate of the third programmable divider is 1/5.

- 25. (Amended) The TV receiving tuner according to claim 4, further comprising:
- a third programmable divider to receive the oscillation signal of the local oscillator and divide the oscillation signal; and
- a fourth mixer to mix the received TV signal and the output of the third programmable divider and frequency convert the received TV signal into an intermediate-frequency signal having a third frequency,

wherein the local oscillator outputs an oscillation signal having a frequency band of at least 803 to 473 MHz, wherein a dividing rate of the second programmable divider is 1/3, and a dividing rate of the third programmable divider is 1/9.

- 26. (Amended) The TV receiving tuner according to claim 4, further comprising:
- a third programmable divider to receive the oscillation signal of the local oscillator and divide the oscillation signal; and
- a fourth mixer to mix the received TV signal and the output of the third programmable divider and frequency convert the received TV signal into an intermediate-frequency signal having a third frequency,
- wherein the local oscillator outputs an oscillation signal having a frequency band of at least 824 to 530 MHz, wherein a dividing rate of the second programmable divider is 1/3, and a dividing rate of the third programmable divider is 1/4.
- 27. (Amended) The TV receiving tuner according to claim 4, further comprising:
- a third programmable divider to receive the oscillation signal of the local oscillator and divide the oscillation signal; and

a fourth mixer to mix the received TV signal and the output of the third programmable divider and frequency convert the received TV signal into an intermediate-frequency signal having a third frequency,

wherein the local oscillator outputs an oscillation signal having a frequency band of at least 767 to 473 MHz, wherein a dividing rate of the second programmable divider is 1/3, and a dividing rate of the third programmable divider is 1/6.

## REMARKS

Applicants have rewritten Claims 1-4, 6-16, and 18-27 for grammatical purposes only. No new matter has been added as a result of this amendment. The changes from the previous version to the rewritten version are shown in attached Appendix A.

In addition, Applicants have enclosed a corrected version of Fig. 3 with corrections marked in red. Applicants request the Examiner approve the corrections and will submit formal drawings upon receiving a Notice of Allowance.

Respectfully submitted,

Gustavo Siller, Jr.

Registration No. 32,305 Attorney for Applicants

BRINKS HOFER GILSON & LIONE P.O. BOX 10395 CHICAGO, ILLINOIS 60610 (312) 321-4200

## APPENDIX A

Attorney Docket No. 9281-4199
TV Signal Receiving Tuner Capable of Outputting Oscillation Signal
Having Wide Frequency Band by Means of Single Local Oscillator
Takeo Suzuki et al.

## In the Claims

Please amend Claims 1-4, 6-16, and 18-27 as follows:

(Amended) A TV signal receiving tuner for receiving TV signals by dividing them-the TV signals into a plurality of frequency bands, comprising:
 a local oscillator which oscillates at a frequency range corresponding to a received TV signal having a predetermined frequency band;

a first programmable divider which receives a local oscillation signal of the local oscillator and divides the local oscillation signal; and

a first mixer which mixes the received TV signal and the <u>an</u> output of the first programmable divider and frequency converts the received TV signal into an intermediate-frequency signal having a predetermined frequency, wherein

a dividing rate of the first programmable divider is variable and set to 1 to receive the <u>a</u> TV signal having a predetermined-<u>first</u> frequency band and to <u>at most</u> 1/2 or less-to receive a TV signal having a <u>second</u> frequency band, the <u>second</u> frequency band being lower than the predetermined-<u>first</u> frequency band.

 (Amended) A TV signal receiving tuner for receiving TV signals by dividing them into a plurality of frequency bands, comprising:

a local oscillator which oscillates at a frequency range corresponding to a received TV signal having a predetermined frequency band;

a second programmable divider which receives a local oscillation signal of the local oscillator and divides the local oscillation signal;

a second mixer which mixes the received TV signal and the local oscillation signal and frequency converts the received TV signal into an intermediate-frequency signal having a predetermined-first frequency; and